



## **P.F.E. 100 SERIES**

### **DESCRIPTION:**

P.F.E. 100 is a water-based semi-gloss Polyethelene Fluorocarbon Acrylic Emulsion that exhibits a very durable, hard and flexible finish for exterior or interior use. It is odorless and dries in one hour under normal weather conditions. P.F.E. 100 exhibits excellent resistance to scrubbing; it withstands a 20,000 scrub cycle test per ASTM D-2486-79. This is the perfect coating for commercial application because it can be touched up, on a clean surface, without having to repaint the entire surface. Most marks can be removed from P.F.E. 100 by scrubbing with soap and water.

### **FINISH:**

Semi-Gloss

### **USES:**

Sheetrock	Stucco	Asbestos
Plaster	Masonry	Built Up Roofs
Concrete Block	Shingles	Shakes
Metal	Wood	

P.F.E. 100 makes an excellent concrete block filler. Add 1¼ pounds of Portland Cement, per gallon, to the first coat of P.F.E 100 and roll on to the cement block to fill all the voids. After adding the cement, the pot life will be about three to four hours. When the block filler coat dries, apply one finish coat of P.F.E. 100, which will result in a good watertight surface.

### **APPLICATION:**

375 Square Feet per Gallon @ 2 Mils

Do not apply under 55°F and protect from freezing.

Apply with roller, brush or spray application.

All surfaces to be painted must be clean and dry. Remove any dirt, grease, wax, soap, paste and any other water soluble materials. Remove any peeling paint, scaling or loosely adhering material and treat any rusted metal with Alphas-40. All metal surfaces should be primed with an anti-corrosive primer; consult with a Preservo Paint technician for the proper type for your project. Glossy surfaces must be dulled with steel wool or sanded. New wood should be primed with an oil base primer. New plaster, concrete or masonry should be thoroughly cured prior to painting.

### **THINNING AND CLEANUP:**

Apply P.F.E. 100 as manufactured or thin with water to achieve spraying consistency. Do not thin in excess of one pint of water per gallon. Clean up all equipment with warm soapy water.

### **AVAILABLE IN:**

Interior Or Exterior, Over 2000 Decorator colors, Federal Standard 595B, Pearlescents And Metallics.