



VINYL ACRYLIC LATEX – VAL - 100

DESCRIPTION:

Vinyl Acrylic Latex is a flat coating for interior or exterior. It is odorless, washable, and dries in one hour or less, under normal weather conditions. Vinyl Acrylic Latex may also be touched up without painting the entire surface. VAL-100 imparts a rich, soft and lusterless finish to any surface it is applied to.

FINISH:

Flat

USES:

Sheetrock	Concrete	Masonry
Plaster	Built-up Roofs	Brick
Stucco	Asbestos	Shingles
Shakes	Metal	Wood

APPLICATION:

300 to 500 Square Feet, Per Gallon, Depending On Surface Porosity.

Do not apply under 55°F and protect from freezing.

Apply with roller, brush or spray application.

All surfaces to be coated must be clean and dry. Remove all dirt, grease, oil, wax, rust, mildew, paste, soap and any other water soluble materials. Remove any peeling paint, scaling or loosely adhering material and treat any rusted metal with Alphas-40. All metal surfaces should be primed with an anti-corrosive primer; consult with a Preservo Paint technician for the proper type for your project. Glossy surfaces must be dulled with steel wool or sanded. New wood should be primed with an oil based primer. New plaster, concrete or masonry should be thoroughly cured prior to painting. If applying two coats, allow the first coat to dry before re-coating.

THINNING AND CLEANUP:

Apply VAL-100 as manufactured or thin with water to achieve spraying consistency. Do not thin in excess of one pint of water per gallon. All spills and splatters should be wiped up immediately with a damp cloth or sponge. Clean up all equipment with warm, soapy water.

AVAILABLE IN:

Interior Or Exterior, Over 2000 Decorator Colors, Federal Standard 595B, Pearlescents And Metallics.