



## VINYL STRIP COAT – VS-2005

### DESCRIPTION:

Vinyl Strip Coat is a one component system designed to be used as a removable masking agent. It is most widely used as a coating for the walls and flooring of spray booths. When Vinyl Strip Coat becomes inundated with paint, it is simply peeled off the walls and floor of the spray booth. The accumulation of paint is removed with the coating.

It may also be used as a masking agent on surfaces resistant to Methyl Ethyl Ketone solvent. An example would be a two-color combination on metal. Vinyl Strip Coat would be used as a mask on areas not to be painted or to be painted with a second color. Another use for Vinyl Strip Coat is a removable coating for glass. Due to its extremely good chemical resistance, it may also be used as a stop-off coating for metal plating.

### FINISH:

Gloss

### USES:

Spray Booths	Temporary Coating	Plating Stop-Off Coating
Masking Agent	Strippable Coating	Glass Coating

### FILM PROPERTIES:

Air Dry Time	20 Minutes @ 77°F
Re-coat Time	40 Minutes @ 77°F

### APPLICATION:

225 Square Feet Per Gallon  
Brush, Roller or Spray.  
Reduce with S-06, MEK solvent for spraying.

### THINNING AND CLEANUP:

S-06 MEK

### AVAILABLE IN:

White And Pastel Custom Colors.  
VS-2002, Clear, By Special Order.